

CDD15J 全电动托盘堆垛车 Electric pallet stacker

产品性能特点:

1. 大功率、高性能起升泵站，操作效率高；
2. 侧驾式设计，转弯半径小，视野广；
3. 永磁电机驱动系统，体积小、质量轻、损耗小；
4. 德国原装进口防水微动开关，适应寒冷、潮湿、粉尘等恶劣环境；
5. 四色显示LED电量表，简单直观；
6. 外置式充电器，散热性能更佳；
7. 超长操作手柄，集成起升按钮、钥匙开关、电量表，符合人机工程学原理，操作简单舒适；加装调速开关，速度控制更精准；采用优质气压式弹簧，自动缓慢复位，经久耐用。
8. 高密度铁丝防护网，偷焊而成，坚固耐用，防护效果优良；
9. 免维护的蓄电池；

Characteristics:


1. High-power and high-performance lifting pump has high efficiency.
2. Side driving design gives the truck a small steering radius and broadened view.
3. The driving system with permanent magnetic motor has small volume, light mass, small loss.
4. Water-proof inching switch imported from German meets the requirements of harsh working condition such as cold, humidity and dust circumstances.
5. Four colors LED electricity meter makes it simple and direct to read.
6. External positioned charger has better cooling performance.
7. It's more comfortable and easy for operation using a super long handle that integrates lifting button, key switch, electricity meter, which is suitable for ergonomics; more accurate speed control with the turbine speed switch; more durable with the high quality air-pressure springs which allows slowly and automatically reset.
8. Iron steel guard with high density is durable, firm and has high protection effect.
9. Maintenance-free battery



CDD15J 全电动托盘堆垛车 Electric pallet stacker

制造商和技术参数 Manufacturer's Data and Design Characteristics

特征 Characteristics		合力(HELI)					
1.1	品牌 Manufacturer	合力(HELI)					
1.2	车型 Model	CDD15J					
1.3	操作方式 Operation	步行式 Pedestrian propelled					
1.4	额定载重能力 Rated traction weight	Q (kg)	1500				
1.5	门架类型 Mast type	单门架 Single mast	两级门架 2-Stage STD				
1.6	堆升高度 Lift	H3 (mm)	1600	2000	2500	3000	3500
1.7	最高点载重 Capacity at highest height	kg	1500	1300	1100	1000	950
1.8	自重(含电瓶) Service weight with battery	kg	430	471	483	495	507
1.9	载荷中心距 Load centre	c (mm)	600				
1.10	前悬距 Axis centre to fork face	x (mm)	720				
1.11	轴距 Wheel base	y (mm)	1167				
轮子 Wheels		Wheels type		聚氨酯 (Polyurethane)			
2.1	轮胎类型 Tyre type						
2.2	驱动轮尺寸 Driving wheel size	Φ × w (mm)	Φ210 × 70				
2.3	承载轮尺寸 Bearing wheel size	Φ × w (mm)	Φ30 × 70				
2.4	平衡轮尺寸 Additional wheels (dimensions)	Φ × w (mm)	Φ115 × 55				
2.5	驱动轮、平衡轮/承载轮数量 (x=驱动轮 y=承载轮) Wheels, number front/rear (x = driver/y = driver)		1x/1x4				
尺寸 Dimensions							
3.1	最低门架高度 Height of mast, lowered	h1 (mm)	2014	1425	1745	1995	2245
3.2	门架最大高度 Height of mast, extended	h2 (mm)	2014	2424	2924	3424	3924
3.3	货叉最低高度 Fork Height, Lowered	h3 (mm)	86				
3.4	整车长度 Overall length	L (mm)	1740				
3.5	车桥长度 Length to fork face	Q (mm)	590				
3.6	整车宽度 Overall width	b1/b2 (mm)	795				
3.7	货叉尺寸 Fork dimensions	s/d1 (mm)	60/160/150				
3.8	货叉外宽 Width of forks	s2 (mm)	570/95				
3.9	货叉中心到前轮轴距 Min.Ground clearance	n2 (mm)	26				
3.10	载重能力: 1000x1200托盘 (1200mm货叉位置) 4800 pallet with pallet	Ast (mm)	2074				
3.11	载重能力: 800x1200托盘 (1200mm货叉位置) 4800 pallet with pallet	Ast (mm)	2040				
3.12	转弯半径 Max. turning radius	Wa (mm)	1342				
性能 Performance							
4.1	行走速度 满载/空载 Travel speed, with/without load	(mm/h)	4.0/4.2				
4.2	堆升速度 满载/空载 Lifting speed, with/without load	(mm/s)	92/138				
4.3	下降速度 满载/空载 Lowering speed, with/without load	(mm/s)	112/58				
4.4	最大爬坡角 满载/空载 Max. gradeability (laden/unladen)	(%)	6/8				
4.5	制动类型 Service brake	电磁制动(Electromagnetic brake)					
电机和蓄电池 Drive and Battery							
5.1	驱动电机功率 Drive motor output	S2 60 min. (kW)	0.75				
5.2	起升电机功率 Lift motor rating	at S3 16% (kW)	2.2				
5.3	蓄电池 根据 DIN 43531/2536 A,B,C, 43531/3930 A,B,C, ZnO		no				
5.4	蓄电池额定容量 Battery will-gas rated capacity	(V/Ah)	2 × 120/100				
5.5	蓄电池重量 (±5%) Battery weight (± 5%)	(kg)	2 × 27				
其他 Others							
6.1	噪音水平 Noise level at operator 's ear	(dB(A))	69				
6.2	转向类型 Steering type	机械转向/Mechanical steering					



HELI 安徽合力股份有限公司
ANHUI HELI CO., LTD.

地址: 中国合肥经开区方兴大道668号
电话: (86 551)83632133, 63646005, 63688900
传真: (86 551)83633431
服务: 4001-600761
网址: http://www.helichina.com

ADD: NO.668 Fangxing Street, Economical Development Zone, Hefei, P.R.China
TEL: (86 551)83632133, 63646005, 63688900
FAX: (86 551)83633431
400 SERVICE: 4001-600761
WEBSITE: http://www.helichina.com

授权经销商 AUTHORIZED DEALER

* 本公司保留更改产品设计规格的权利，恕不另行通知。
* Our products are subject to improvements and changes without notice.