




1-5ton AC ELECTRIC PLATFORM TRUCK



Interactive Multifunctional Display



Optional auto water-filling battery (Optional)



Energy regeneration



Energy regeneration with AC technology control for the energy-saving, the single shift working time of the battery is increased by 15%

↑ 15% THE SINGLE SHIFT WORKING TIME OF THE BATTERY IS INCREASED BY

Reliable multifunctional display showing working condition, fault detection information for more direct and convenient reading.

Technical Parameters

Item	unit	G series 1-5t AC Electric Platform Truck							
1 Truck Model		BD10-JB1	BD20-JA1	BD20-JB1	BD30-JA1	BD30-JB1	BD40-JA1	BD50-JA1	
2 Operating mode		Seated							
3 Capacity	t	1	2	2	3	3	4	5	
4 Wheelbase	mm	1150	1650	1650	1650	1650	1810	2100	
5 Weight	kg	880	1500	1500	1500	1500	2200	2400	
6 front-rear tires load without load	kg	440/440	800/700	800/700	800/700	800/700	1000/1200	1150/1250	
7 Type		Pneumatic tires							
8 Tires Front tire		5.00-8	6.50-10	6.50-10	6.50-10	6.50-10	7.00-12	7.00-12	
9 Rear tire		5.00-8	6.50-10	6.50-10	6.50-10	6.50-10	7.00-12	7.00-12	
10 Seat height(front ground)	mm	735	860	860	860	860	980	980	
11 Traction base height	mm	450(Optional)	580(Optional)	580(Optional)	580(Optional)	580(Optional)	720(Optional)	720(Optional)	
12 Truck dimension(length*width*height)	mm	2750*1000*1225	3615*1400*1400	3615*1400*1400	3615*1400*1400	3615*1400*1400	3970*1500*1500	4575*1500*1500	
13 Platform dimension(length*width*height)	mm	1400*1000*560	2240*1400*680	2240*1400*680	2240*1400*680	2240*1400*680	2600*1500*850	3200*1500*850	
14 Min. Ground clearance	mm	80	130	130	130	130	120	120	
15 Turning radius	mm	3000	3100	4300	3100	4300	4400	4600	
16 Driving speed(without load)	km/h	8.0/10.0	12.0/16.0	12.0/16.0	12.0/16.0	12.0/16.0	12.0/15.0	12.0/15.0	
17 Gradability(with load)	%xm	10%/x20m	10%/x20m	10%/x20m	10%/x20m	10%/x20m	10%/x20m	8%/x20m	
18 Driving brake		Hydraulic brake and electric brake							
19 Parking brake		Mechanic							
20 Driving mode		Rear drive							
21 Drive motor rated power	kw	3	4	4	5	5	6	6	
22 Steering motor rated power	kw	/	1.35	/	1.35	/	1.35	1.35	
23 Battery(rated capacity(5H))	V/Ah	24/280	48/280	48/280	48/280	48/280	48/350	48/450	
24 Battery weight	kg	300	550	550	550	550	579	715	
25 Tread, front tire	mm	790			1160			1250	
26 Tread, rear tire	mm	820			1160			1250	
27 Driving control mode		Electronic stepless mode							
28 Operator's ear noise	db(A)	<65							
29 Controller type		CURTIS AC controller							

Standard configuration

Standard configuration	Optional configuration
Streamlined glass fiber cover	Took kits
Battery	Cabin
Liquid crystal combination display	Platform guard bar
Pneumatic tires	Beacon
Traction pin	Crate
	Optional dimension platform
	Immotion controller



ANHUI HELI CO., LTD.
 ADD: NO. 668 Fangqiang Street, Economical & Development Zone, Hefei, P.R. China
 Sales hotline: (0086) 551-63689674
 (0086) 551-63689674
 (0086) 551-63689676

Free hotline: 4001600761
 FAX: (0086) 551-63689673
 (0086) 551-63689674
 E-mail: heli@heli-china.com
 Web site: www.heli-china.com

© 2018 heli copyright
 Catalog No.110119 HELI Pin



1-5 ton G Series AC ELECTRIC PLATFORM TRUCK

HELI
 LIFTING THE FUTURE



» Brief Introduction

As the newly designed environmentally friendly tractor machines, HELI G series 1-5T AC Electric Platform Truck has the unique profiling, ergonomically and aesthetic philosophy combination for operator comfort and ease of use, maintenance convenience.

This machine is powered by battery, with World-famous Curtis AC controller matched AC motors to supply the stepless accelerating, high efficiency, reliable quality, comfortable operation, and strong power.




Drive system

- Special drive axle for electric machines with low noise, non-pollution, stable running, perfect sealing, and also with enough ground clearance for good trafficability.
- Large gear ratio, powerful traction, strong gradeability, perfect performance, suitable for complex operating condition.

Steering system


- With fully-hydraulic Transverse cylinder power steering or circulating ball type redirector, easily steering, and long working life.
- Front and rear suspension are with elastic connection for more comfort.



Optional Equipment—Cabin



Optional Equipment—Platform guard bar



Superior intelligent design

- Intelligent components and function for the better safety to driver and machines, also supply the higher working efficiency, and reduce the energy-consumption.

Operating system

- Comfortable brake/accelerating pedal position with light stepping strength, fully meeting ergonomically demands.
- With front-rear adjustable steering wheel to satisfy different height drivers. With excellent cold-brake efficiency, enough brake force, fully meet the parking and driving brake standard.

Chassis system

- Side-extraction battery replace, very convenient and reliable.

