



HELI

FORKLIFT

内燃平衡重式叉车
BALANCE WEIGHT TYPE FORKLIFT

SPECIFICATIONS

型号	Model		CPCD120-WX-06 CPCD120-CU-06	CPCD120-WX-09 CPCD120-CU-09	CPCD135-WX-06 CPCD135-CU-06
载荷中心	Load Centre	mm	600	900	600
起升重量	Rated Load	kg	12000		13500
起升高度 (标准) h3	Lift Height (standard)	mm	3000		
起升速度 (满载)	Lifting Speed (loaded)	mm/s	350		
下降速度 (满载)	Lowering Speed (loaded)	mm/s	370		
门架倾角 (前/后)	Mast Tilt (fwd/bwd)	Deg	6/12		
行驶速度 (满载/空载)	Travel Speed (loaded/unloaded)	km/h	28/29		
最小转弯半径	Min. Turning Radius	mm	4400	4500	
最大爬坡度	Gradeability	%	28		
外型	全长 (含货叉) L1 Overall Length (with Fork)	mm	5820	6420	5820
	全宽 B Overall Width	mm	2520		
	全高 (门架不起升) h1 Overall Height (at Mast)	mm	3300		
轴距 L5	Wheelbase	mm	3000		
轮距 (前/后) S/P	Tread (fwd/bwd)	mm	1950/2050		
悬距 (前/后) X/L4	Overhang (fwd/bwd)	mm	780/820		
最小离地间隙	Min. Under clearance	mm	215		
货叉 Fork	调距范围 R	Space	500-2370		
	长度 L3	Length	1220	1820	1220
	宽度/厚度 W/T	Width/Thickness	200/85		
发动机 Engine	发动机制造商/型号	Type	Cummins QS86.7 / Wuxi CA6110/125Zi-HL20 diesel engine		
	缸数/排量	Cyl. Number/ Displacement	/L 6/6.7 / 6/7.127		
	额定功率/转速	Rated Power/Rated Speed	kW/rpm 119/2200 / 117/2200		
	最大扭矩/转速	Max. torque/Rotate Speed	Nm/rpm 730/1400 / 590/1600		
	油耗	Fuel Consumption	g/kWh ≤211 / ≤235		
	变速箱	Transmission	Electric-hydraulic control box for HELI		
轮胎 Tye	前轮	Front	11.00-20		
	后轮	Rear	11.00-20		

CPCD120-135



安徽合力股份有限公司
ANHUI HELI CO., LTD.